


LED LUMINAIRE

B12-0540-X1M



Description

B12-0540-X1M - is a LED luminaire for illumination of entrances and other housing and utilities sector premises.

The luminaire is vandal-proof protection and can be installed in public places where significant loads, vibrations and shocks are possible.

Protection rating IP54, that guarantees dust and moisture protection, reliability and long lifetime.

The case construction allows the luminaire to be mounted to the ceiling or wall surface and makes it difficult to remove the luminaire without permission as during the stealing its case is damaged.

Benefits

- No flicker of light
- Class of protection against electric shock: II
- Long service life
- Durability, stability of luminous flux
- Does not require maintenance
- Does not require special disposal
- Vandal-proof protection
- Protection rating IP54, which guarantees protection against dust and humidity
- 5 years warranty


Application

- Porches • Pavilions • Recreational areas • Local illumination • Building entrances



Specifications

Luminous flux	500 lm
Color temperature	4000 K
Power	5 W
Colour rendering index CRI (Ra)	> 80
Power factor	not normalized
Ripple factor of light	not more 1%
Input voltage AC	175 V - 276 V, 50 Hz
Range ambient temperature	from -10°C to +50°C
Life cycle, no less	50 000 hours
Type of diffuser	opal
Protection rating	IP54
Dimensions	145x235x18 mm
Weight	0.25 kg

Light distribution curve



Dimensional drawing



The manufacturer reserves the right to make changes in the product design, if such changes do not lead to the deterioration of the declared characteristics, without prior notice. Current technical information is published on the website www.vtnled.com.